



ABRASIVES CHEMICALS & MACHINES

FOR

CONCRETE POLISHING

& MARBLE, GRANITE, STONE, TERRAZZO, TILE

WE PROVIDE SOLUTIONS

Mr. AALOKE SURIE (Founder)

Surie Porex was established in 1985, by our Founder Mr. Aaloke Surie. He is a Mechanical Engineer trained in IIT-Mumbai and RWTH-Aachen Germany. His vision was to become the market leader and provide high quality, innovative and sustainable products that empower our customers.




Mr. SACHIN SURIE (CEO)

Mr. Sachin Surie is the Chief Executive Officer. He is a Mechanical Engineer from the Ohio State University, USA. He joined the company in 2004 and has 21 years of experience in designing, developing and manufacturing abrasives, machines and chemicals for all types of surfaces.




SCALE OF MANUFACTURING



3 Factories



1000+ Employees



10+ Product Lines.



PRODUCT RANGE

Surie Porex products include Diamond Pads, Diamond Abrasives, Silicon Carbide Abrasives, Floor Polishing Machines, Stone Glues, Epoxy Resins, Polyester Resins, Penetrating Sealers, Densifiers, Hardeners, Waxes and Cleaners for Laying, Installation, Polishing, Protection, Treatment, and Maintenance of Marble, Granite, Concrete and Terrazzo.



NETWORK

Surie Porex has an excellent network of sales and distribution in all parts of India and is now looking to expand its network abroad to sell its extensive range of Granite, Marble and Concrete Polishing products. With complete in-house technology SURIE POLEX is in a position to adapt to different market requirements.



HSP - 650 PLANETARY FLOOR GRINDER
3&4 HEAD VERSIONS

Motor 10HP, 3 Phase
Working Width 650mm
Speed 100-1500rpm
Weight 280kg (3 Head)
307kg (4 Head)



HSG - 630 ROTARY FLOOR GRINDER

Motor 12HP, 3 Phase
Working Width 630*630mm
Speed 100-1450rpm
Weight 256kg



HSG - 500 GEARED GRINDER

Motor 10HP, 3 Phase
Working Width 480*480mm
Speed 100-1500rpm
Weight 256kg



HSG - 300 FLOOR GRINDER

Motor 5HP, 3 Phase/5HP, 1 Phase
Working Width 310*550mm
Speed 100-1500rpm
Weight 170kg



FG - 250 VFD FLOOR GRINDER

Motor 5HP, 1 Phase
Working Width 250mm
Speed 0-1440rpm
Weight 72kg



FG - 250 FLOOR GRINDER

Motor 5HP, 3 Phase
Working Width 250mm
Speed 1440rpm
Weight 82kg



EP - 200 FLOOR POLISHER

Motor 2HP, 3 Phase
Working Width 200mm
Speed 720rpm
Weight 125kg



CONCRETE GRINDING, POLISHING AND CLEANING MACHINES

FPM - 330 FLOOR GRINDING MACHINE

Motor 5HP, 3 Phase
Working Width 330mm
Speed 450rpm
Weight 130kg



MINI POLISHER

Motor 1HP, 1Phase
Working Width 200mm
Speed 400rpm
Weight 50kg



CONCRETE SCARIFIER

Motor 7.5HP, 3Phase
Drum Width 200mm
Cutter 78
Weight 117kg



2.5HP SINGLE DISC DIAMOND POLISHER

Motor 2.5HP, 1Phase
Working Width 430mm
Speed 175rpm
Weight 50kg +
(12.5X2)25kg



FPM - 400 FLOOR PREPARATION MACHINE

Motor 5HP, 3 Phase
Working Width 400mm
Speed 720rpm
Weight 130kg



FG - 400 FLOOR GRINDER

Motor 5HP, 3 Phase
Working Width 400mm
Speed 720rpm
Weight 110kg



HSB - 500/430 HIGH SPEED BURNISHER

Motor 5Hp, 3Phase/
5HP, 1Phase
Working Width
500/430mm
Speed 100-1440rpm
Weight 162kg



HIGH SPEED BURNISHER

Motor- 2HP, 1Phase
Working Width- 500mm
Speed- 100-1500rpm
Weight- 50kg



AUTO SCRUBBER

Power 1600w
Voltage 220v/50hz
Tank Clean Water 27l
Dirty Water 31l
Speed 148rpm
Weight 69kg



INDUSTRIAL DUST COLLECTOR 60L, 3 MOTOR

Power 2000/3000W
Voltage 220V
Vacuum 250mbar
Air Flow Volume 159L/Sec
Drum-Stainless Steel
Weight 28 kg
Available in 15, 30 &
60L 2 Motor



INDUSTRIAL DUST COLLECTOR WITH SQUEEZE - 80L, 3 MOTOR

Power 3000w
Voltage 220v
Vacuum 250mbar
Air Flow Volume 120L/Sec
Drum Stainless Steel,
Weight 36kg



DUST COLLECTOR

Motor 5hp, 3phase
Voltage 415v
Vacuum 300mbar
Pressure 300ft3/min
Pipe Dia 45mm
Weight 170kg





Celebrating
40
YEARS
1985 - 2025

CONCRETE LAYING AND POLISHING MACHINES

RIDE ON TROWEL POLISHING SYSTEM



RIDE ON TROWEL 36" SPRT-236LR


Model 36" Low Rider
Engine Honda GX690
Working Dia 1870mm
Max Speed 150rpm
Tank 17 Ltr
Weight 280Kg

PLANETARY POLISHING ATTACHMENT FOR RIDE ON TROWELS



Surie Pox's Planetary Trowel Polishing System is designed for polishing concrete with ride-on power trowels and walk behind power trowels and is ideal for use on large industrial and warehousing projects.

MAIN FEATURES OF OUR TROWEL POLISHING SYSTEM



Speed: Our system is very fast: You can fully polish 10,000 sqft per day per ride-on power trowel.
Cost-Effective: There is no need to buy new machines and equipment. You can use your existing power trowel. All you need is one set of our planetary trowel polishing system and diamond pads.
Adaptable: Our Trowel Polishing System is available in various sizes. This allows it to be used with any ride-on power trowel available in the market. Our system will transform your ordinary power trowel into a planetary concrete polishing machine.
Planetary: Our planetary plates are installed on the floating pans. They have bearings which allow for a free/passive planetary movement.
Finishes: You can achieve various finishes: low, medium or high gloss. You can also achieve various grades of aggregate exposure.
Easy: Our system allows for very easy tool changes with our high quality diamond pads. See our "how to polish" chart below.
Balance: Our system provides balanced movement and even tool wear.

PLANETARY TROWEL TOOL HOLDERS



PANS



BLADE SETS



ABRASIVES VELCRO PLATE

Our Tools System are offered in three styles: 355mm Foam Plates with hook and loop attachment for 900mm pans, and 275mm Foam Plates with hook and loop attachment for 750mm pans, 240mm Foam Plates with hook and loop attachment for 600mm pans.

POWER TROWEL


Model- QJM-1000
Engine Honda- GX160
Working Width- 915mm
Max Speed- 100-140rpm
Weight- 83kg



CONCRETE LAYING MACHINES

DUO SCREED WALK BEHIND

Model- JG-100 Screed- 2.4m
Engine- Honda GX35
Handle- 50 dBA
VPM- <9m/s sq
Weight- 12.7kg



TOPPING SPREADER

Model- JG-1000S
Hopper Size- 100kg
Discharge Range- 1-6kg
Working Width- 1000mm
Wheel- 2
Weight- 60kg



EDGER TROWEL

Model- 424E
Engine- Honda GX160
Working Width- 610mm
Max Speed- 135rpm
Weight- 54kg



sales@suriepox.com, www.suriepox.com

DIFFERENT TYPE OF METAL BONDS

CHB FOR SOFT CONCRETE

CHB – Specially designed hard bond metal grinding tool for soft concrete. As soft concrete is more abrasive, these CHB tools give more coverage with lesser abrasion of tool grits.

Available in grit: 25/36/60/120/200.

Concrete type – Soft Floors.

CHC FOR MEDIUM SOFT CONCRETE

CHC is a medium hard bond for grinding of medium soft concrete.

Available in grit: 25/36/60/120/200.

Concrete type - Medium soft floors.

AH FOR MEDIUM CONCRETE

AH– for giving better coverage on medium hard concrete AH is specially designed metal bond tool for free & smooth grinding.

Available in grit: 25/36/60/120/200. Concrete type – Medium Floors.


CSE FOR HARD CONCRETE

CSE- Specially designed soft bond metal grinding tool for hard concrete. CSE metal grinding tool ensures smooth grinding on hard floors.

Available in grit: 25/36/60/120/200.

Concrete Type – Hard Floors.

AVAILABLE IN ALL SHAPES FOR SURIE POLEX MACHINES



DSMA



DSMA-C



DSMA PCD SCRAPER



DSMB

AVAILABLE IN ALL SHAPES FOR OTHER MACHINES IN THE MARKET



DHMA



DKQMA



DSTMA



DTC



DTMA



DBDMA



DTMA PCD SCRAPER



DFMVW-M0

DFMVW

METAL BOND DIAMOND 'W' SERIES

METAL BOND 'W' SERIES - Economically designed tool for adhesive removal and grinding rough surfaces. Available in OK. (Coarse Grinding).

PCD TOOLS

PCD Scraper – Best tool for epoxy & coating removal. Available in single & double PCD inserts.



DSMA PCD

DTPCD

HYBRID DIAMOND ABRASIVES & PADS



DFMRW-OK-CHIPS



DCRMRA

This tool is a combination of metal and resin bond diamond. These tools are in Frankfurt shape or with hook and loop backing that can be fitted to a floor grinding machine. It is ideal for smoothing the scratch pattern. It is very effective for grinding the soft concrete.

Available in - OK /36/60/120/200.


CONCRETE GRINDING METAL BOND DIAMOND ABRASIVES & PLATES



DFME-C



DFMX




DKMA




DCMPD 4"



DCMPD 7"



DJMA




DJMA-C




DCMA




DST J3M



DK 200



DK 240





DGP 240



DSP 250

ADAPTER PLATES FOR ALL MAKES



DBP 250

BUSH HAMMERS AND ROLLERS

BUSH HAMMER
ROLLER



BUSH HAMMER
3 ROLLER



GRINDING
ROLLER SPIKEY




GRINDING
ROLLER ABRABE



GRINDING
ROLLER DIA ABRABE




DSMA BUSH
HAMMER




FF GRINDING
ROLLER SPIKEY



FF GRINDING
ROLLER ABRABE



FF GRINDING
ROLLER DIA ABRABE



It's a bearing mounted tool that can be fitted to a floor grinder or a hand polisher for giving concrete a bush hammered texture on the top layer. It can be used for breaking epoxy / paint coating on the floor. Available in - 7" 3 Roller Plate for Hand Polisher and in Frankfurt, Fickert and other Shapes for floor grinder.

sales@suriepolex.com, www.suriepolex.com

DIFFERENT TYPE OF RESIN BONDS

CONCRETE SERIES

Concrete Series is a very aggressive tool for dry polishing of concrete gives excellent gloss and clarity. Specially designed formula gives optimum coverage and highest gloss on concrete.

Available in grit: 60/100/200/400/800/1500/3000 and available in all shapes shown below.

CONCRETE-ECO SERIES

Concrete Eco Series is an economically designed concrete polishing resin bond polishing pads give good coverage and gloss. Available in grit: 60/100/200/400/800/1500/3000 and available in all shapes shown below.


XD SERIES

XD Series is an all surface grinding pad. It is economically priced as compared to concrete pads. These pads are aggressive in action and has good coverage and gloss. It can be used on concrete and terrazzo floors.

Available in grit: 60/100/200/400/800/1500/3000 and available in all shapes shown below.



AVAILABLE IN ALL SHAPES



DCRF2-3U1 Ø50 X 2.75mm	DCRF3-5S1 Ø80 X 2.75mm	DCRF3 3U1 Ø80 X 5.00mm	DJ3R Ø80 X 11.00mm	DJ4RT Ø100 X 15.00mm	DJ4R TURBO Ø100 X 15.00mm	DCRF 7U2 Ø100 X 2.75mm	DCRF 4U2 Ø100 X 5.00mm	DCRF 5U3 Ø100 X 3.50mm	DCRF5-9U1 Ø125 X 3.00mm	DCRF6-9U1 Ø150 X 3.00mm	DCRF7-6S1 Ø175 X 3.00mm
------------------------------	------------------------------	------------------------------	--------------------------	----------------------------	---------------------------------	------------------------------	------------------------------	------------------------------	-------------------------------	-------------------------------	-------------------------------

TROWEL POLISHING PAD



DCRF-6S2-B, 100*3.00mm

Specially designed concrete pads for Trowel polishing system can be used both wet & dry. Application gives better coverage and gloss with Trowel Polishing System. Available in - 0/1/2/3/4/5/6

EDGE POLISHING PADS



DCRPD, 100*3.00mm



DCRB (SNAIL), 100*3.00mm

Edge Polishing Diamond Pads 1. Zero vibration while polishing. 2. Low operator fatigue. 3. No extra coupling required. 4. Replacement for GC wheels. 5. Replacement for flexible Diamond Pads. 6. Replacement for conventional CRB abrasives. 7. Faster speed of polish. 8. Polishes dry at high speed. 9. Even polishes the surface of granite because lock nut is below the surface.

SPARES, ANCILLIARIES & HAND POLISHERS



VELCRO ADAPTER
HOOK & LOOP



DSMA
VELCRO ADAPTER



VELCRO ADAPTER
FOR ELECTRIC DRILL



CRB
COUPLING FLAT

HAND POLISHER

Working Width-
100mm
Speed-1200rpm
Weight-2kg



ANGLE GRINDER


Working Width-
100mm
Speed- 11000rpm
Weight- 2kg



CLEANING, BUFFING PADS & BRUSHES



DIAMOND FLOOR PADS



AVAILABLE IN 4, 8, 13 & 17"
BUFFING AND CLEANING PADS



AVAILABLE
IN 4, 13, & 17"
SOFT, HARD & WIRE BRUSHES



CONCRETE CARE CHEMICALS AND CLEANERS

DENSI HARD® LITHIUM SILICATE

It is a lithium silicate-based deep-penetrating treatment for concrete and terrazzo floors. It creates a hard, polishable surface with high reflectivity, reduces maintenance and dusting, improves abrasion resistance, and minimizes wear on diamond abrasives. Eco-friendly and long-lasting.



DENSI HARD® SODIUM SILICATE

Sodium silicate-based, shallow-penetrating treatment for concrete and terrazzo. It hardens the surface, enhances reflectivity and abrasion resistance, reduces dusting, maintenance, and diamond abrasive wear. Eco-friendly.



DENSI HARD® LS+

Densi Hard LS+ is a lithium-based deep penetrating concrete densifier. It enhances abrasion resistance, boosts gloss and reflectivity when polished, reduces maintenance costs, and penetrates concrete pores for long-lasting protection.



STAIN PROTECTOR CONCENTRATE

Stain Protector Concentrate is a breathable, partly penetrating and film-forming sealer that protects concrete from stains, moisture, oil, dirt, and wear while enhancing durability and appearance.



CREAM WAX

A high-quality concentrated paste wax for concrete, marble, granite, and similar stones. Provides excellent polishing, a super-gloss finish, slight anti-stain, and water-repellent effects. Ideal for final buffing. Available in natural and grey.



SHINER

This is a high quality wax based shiner used for polishing edges, moldings & skirting. Gives high gloss when used with final buff or white pad. Suitable for indoor & outdoor application.



STAINEX

Stainex is a premium solvent-based, deep-penetrating sealer that protects absorbent surfaces like concrete, marble, and sandstone from dirt, oil, and water stains. UV-resistant, breathable, and suitable for indoor and outdoor use.



FLOOR CLEANER NEUTRAL

Floor Cleaner is highly concentrated pH balanced cleaner. Can be used for regular maintenance of marble, granite, stone and tile. Maintains high gloss on floor, can be used with regular mop with scrubbing machine. pH balance ensures no residual effect.



CONCRETE COLOR DYE

Concrete Color Dyes are designed for polished and exposed concrete, offering deep penetration for long-lasting color. They can be used as a base, touch-up, or layered to create unique, mottled effects.




FLOOR CLEANER HEAVY DUTY

Floor Cleaner Heavy Duty is a concentrated oil and grease stain remover. This is a citrus fragrance product which does not contain any harmful chemical, is ideal for the quick and effective cleaning of greasy and oily surfaces.




AVAILABLE SHADES (SPECIALLY DEVELOPED FOR POLISHED CONCRETE)



sales@suriepoxx.com, www.suriepoxx.com

3" CUP WHEELS & 4-5" DIAMOND SAW BLADES

CUP WHEEL
80 mm



FLAT CUP
105 mm



CONTINUOS
100 mm



10 SEG.
100 mm




9 SEG.
100 mm



8 SEG.
100 mm



CONTINUOS
100 mm



10 SEG.
125 mm



BRUSHES ABRASIVES FOR TEXTURE FINISH

R1 - FICKERT

DIAMOND



F- FRANKFURT



CRB & BCRN CHAMFERING




8" CHAMFERING BRUSH



B - BUTTERFLY




SILICON



WIRE



CLEANING



B-FELT

FF-FELT

VACUUM BRAZED GRINDING/PROFILE WHEEL & ENGRAVING TOOLS

FULL ROUND



HALF ROUND



PARALLEL



V SHAPE



ROMAN



HYPOTENUSE



XBQDS



CUTTING AND GRINDING WHEELS & FLAP DISC

CUTTING WHEELS

SINGLE NET
4-5-7-14"

2 NET
4-14"



FLAP DISC
4"



GC WHEEL
4"



DC WHEEL

B SERIES
4"



DC WHEEL

G SERIES
4-5-7"



WA WHEEL
4"






SINGLE & TWO NET 14" CUTTING WHEEL








HOW TO POLISH CONCRETE FLOORS












HOW TO DENSIFY (DUST-PROOF) LEVEL FLOORS

SN	PROCEDURE	ITEM CODE	PHOTO	REMARKS
1	Lightly grind the floor with flexible diamond pad DCRF-200.	DCRF-200		This is done to open up the pores of the concrete. This step is essential for Densifier penetration.
2	Apply the Densifier on the concrete floor.	Densi-Hard Lithium Silicate/Sodium Silicate		Apply with microfiber mop and spread uniformly. Apply more where required.
3	Burnish with flexible diamond pad 800.	DCRF 400/800		Use diamond pad with a high speed burnisher.














HOW TO DENSIFY (DUST-PROOF) UNEVEN FLOORS

SN	PROCEDURE	ITEM CODE	PHOTO	REMARKS
1	Grind the floor with metal bond 200 grit.	DSMA C-200		This is done to open up the pores of the concrete. This step is essential for Densifier penetration.
2	Grind the floor with resin bond 100 grit till the floor is scratch free.	DCRF-7U2 R-100		The 100 Resin is used to remove the scratches of Metal Bond 200 grit.
3	Grind the floor with resin bond 200 grit till the surface is smooth.	DCRF-7U2 R-200		This step is essential to ensure no scratches remain after Densification.
4	Apply the Densifier on the concrete floor.	Densi-Hard Lithium Silicate/Sodium Silicate		Apply with micro fiber mop and spread uniformly. Apply more where required.
5	Burnish with flexible diamond pad 400.	DCRF-7U2 R-400		Use diamond pad with a high speed burnisher.

HOW TO POLISH CONCRETE

SN	PROCEDURE	ITEM CODE	PHOTO	REMARKS
1	Grind the floor with metal bond 120 grit. For uneven floors also use 36 and 60 grit.	DSMA C-120		A good level is a prerequisite for good uniform final finish. Improper first grinding will lead to a patchy finish.
2	Grind the floor with metal bond 200 grit (Ideal to start with this step on level floors).	DSMA C-200		Minor level differences and the scratches of Metal Bond 200 grit was removed.
3	Grind the floor with flexible diamond pad 100 grit.	DCRF-7U2 R-100		The 100 Resin is used to remove the scratches of Metal Bond 200 grit.
4	Grout the floor to repair pinholes and cracks.	Grout Repair		Grouting is done using a mixture of cement, latex, water and concrete dust from the dust collector.
5	Grind the floor with resin pad 200 grit till the floor is scratch free.	DCRF-7U2 R-200		This step is essential to ensure no scratches remain after Densification.
6	Apply the Densifier on the concrete floor.	Densi-Hard Lithium Silicate/Sodium Silicate		Apply with Micro fiber mop and spread uniformly. Apply more in areas where penetration is faster.
7	Grind the floor with flexible diamond pad 400 grit.	DCRF-7U2 R-400		This step will give a nice smooth finish to the floor. A light gloss appears.
8	Polish the floor with resin bond 800 grit.	DCRF-7U2 R-800		A dull shine will appear but the reflection will be sharp. This is essential for sharp final finish. Color and gloss both increase.
9	Polish the floor with resin bond 1500 grit.	DCRF-7U2 R-1500		Both color and sharpness improve substantially after this step.
10	Burnishing with flexible diamond pad DCRF 3000.	DCRF-7U2 R-3000		Use the Diamond Pad with a High Speed Burnisher. A high gloss will appear after this step. Reflection will be sharp.
11	Apply Stain Protector and burnish with white pad 4100/ 4200 grit.	White Pad & Stain Protectant		Gives a brilliant high shine and protects the floor from stains.

HOW TO DYE & POLISH CONCRETE

SN	PROCEDURE	ITEM CODE	PHOTO	REMARKS
1	Grind the floor with Metal Bond 120 grit. For uneven floors also use 36 and 60 grit.	DSMA-C-120		A good level is a prerequisite for good uniform final finish. Improper first grinding will lead to a patchy finish.
2	Grind the floor with Metal Bond 120 grit (Ideal to start with this step on level floors).	DSMA-C-200		Minor level differences and the scratches of metal bond 120 grit was removed.
3	Grind the floor with flexible diamond pad 100 grit.	DCRF-7U2 R-100		The 100 Resin is used to remove the scratches of metal bond 200 grit.
4	Grout the floor to repair pinholes and cracks.	Grout Repair		Grouting is done using a mixture of cement, latex, water and concrete dust from the dust collector.
5	Grind the floor with Resin Pad 200 grit till the floor is scratch free.	DCRF-7U2 R-200		This step is essential to ensure no scratches remain after densification.
6	Apply the densifier on the concrete floor.	Densi-Hard Lithium Silicate/Sodium Silicate		Apply with microfiber mop and spread uniformly. Apply more in areas where penetration is faster.
7	Grind the floor with flexible diamond pad 400 grit.	DCRF-7U2 R-400		This step will give a nice smooth finish to the floor. A light gloss appears.
8	Apply the first coat of Surie Poxex Color Dye (on hard concrete apply 1st coat before densifier.)	Surie Poxex Color Dye. see color chart for all colors.		Ready to use can be applied with spray or paint roller.
9	Polish the floor with flexible diamond pad 800 grit.	DCRF-7U2 R-800		A dull shine will appear but the reflection will be sharp. This is essential for sharp final finish. Color and gloss both increase.
10	Apply the second coat of Surie Poxex Color Dye.	Surie Poxex Color Dye. see color chart for all colors.		Ready to use can be applied with spray or paint roller.
11	Polish the floor with flexible diamond pad 1500 grit.	DCRF-7U2 R-1500		Both color and sharpness improve substantially after this step.
12	Burnishing with diamond flexible pad DCRF-3000 grit.	DCRF-7U2 R-3000		Use the diamond pad with a high speed burnisher. A high gloss will appear after this step. Reflection will be sharp.
13	Apply Stain Protector and burnish with white pad 4100/ 4200 grit.	White Pad & Stain Protectant		Gives a brilliant high shine and protects the floor from stains.

NOTE: For finest finish ensure scratch-free surface before application of densifier. After Densification scratch removal is very tedious. Level grinding is not a solution for pour casting of concrete floors. SURIE POLEX recommends dry grinding and dry polishing on concrete. A dust collector needs to be used in tandem with the concrete grinding machine to ensure best results. Densifiers are applied on dry floors. With dry grinding there is no need to arrange for water or remove sludge. Simply empty the dust collector drum. 28 Days curing recommended for concrete floors for best result. Contact us for technical queries.

Today laying of a concrete floor, keeping in mind that flooring constitutes about 25% of the cost of the project, has become very scientific. Very efficient methods have been developed and continue to be developed to obtain a long lasting surface which provides for all material movements without damage to material handling equipment. As the level of robotisation increases, the importance of the concrete floor will increase.

So please consult concrete flooring experts before budgeting for your flooring in your Warehouse, Factory or Institution. An initial higher cost will be compensated by major savings over the years.

SURIE[®] POLEX

Celebrating
40
YEARS
1985 - 2025

**THE ONE STOP SHOP FOR
EVERYTHING TO POLISH, INSTALL
& MAINTAIN MARBLE, GRANITE,
STONE, TERRAZZO, CONCRETE & TILE**

DIAMOND POLISHING ABRASIVES



STONE CARE CHEMICALS



FLOOR GRINDING AND POLISHING MACHINES



CUTTING AND GRINDING TOOLS & ABRASIVES



FOLLOW US ON SOCIAL MEDIA



OUR BRANDS

सुरी पोलिक्स

SURIE[®] POLEX

सुरी पोलिक्स

SURIE[®] POLEX

SURIE[®] POLEX

since 1985
Innovating
Everyday

सुरी पोलिक्स

Gril
bex

GLOEX[®]

MIRREX[®]

VISA[®]

LapPex[™]

Lap
pex

FIVE STAR[®]

FOR CATALOGUE,
CLICK ON QR HERE
TO OPEN WEBSITE,
GO TO DOWNLOADS



HEAD OFFICE

NEW DELHI

SURIE POLEX INDUSTRIES LLP
4, LSC, Naraina,
Ring Road, New Delhi-110028
INDIA. Tel: +91-11-40776777
Mob: +91-9810119790

BRANCH OFFICE

BANGALORE

SURIE POLEX INDUSTRIES LLP
17/40, 6th Cross, Bannerghatta
Road, Rangadasapa Nagar,
Bengaluru (Karnataka)-560030
INDIA. Tel: +91-80-22225700
Mobile: +91-9845222074

TECHNICAL & MARKETING

SUPPORT

Jalore, Kishangarh, Rajsamand,
Abu Road, Karimnagar, Srikakulam,
Ongole, Martur, Chittoor,
Warangal, Krishnagiri, Shoolagiri,
Igani, Tumkur & Iikal

CLICK HERE TO SEE
OUR DEMO VIDEOS
ON YOUTUBE



Contact Us: Tel: +91-11-40776777, Email: sales@suriepolex.com, Web: www.suriepolex.com