

MADE IN INDIA

Technical Data Sheet

BOTTOM SURFACE SEALER



Description

Bottom Surface Sealer is a specially formulated deep penetrating sealer that prevents moisture from entering the stone from below after it has been laid. It may be used for interior or exterior application.



Areas of Application:

It can be used on the bottom surface of all natural and composite stones such as marble, granite, limestone, sandstone, terrazzo, concrete etc.



Technical Data

Coverage: 1-15m²/Ltr depending upon the absorption coefficient of the stone.

Shelf Life: 2 years



Color

Colorless.



Instruction for Use

1. Clean the surface with SURIE POLEX Floor Cleaner-Neutral. The surface must be absolutely clean and dry before application.
2. Shake the container before using. Do not dilute or mix with other products.
3. Prepare a small test patch to check coverage.
4. Apply evenly and fully with a brush, roller, sponge, spraying device or fluff free cloth & leave it for 10 mint then. Remove surplus material with suitable cloth or fabric.
5. To ensure deep penetration apply 2 to 3 coats.
6. Repellency begins after a few minutes but the product is fully cured after 24 hours.
7. After the cure period the stone can be laid on the floor.



Packaging

Available in 1 Ltr cans.



Disclaimer

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check. Surie Porex accepts no liability for improper use of its products.