

## Technical Data Sheet

# BOTTOM SURFACE SEALER



### Description

Bottom Surface Sealer is a specially formulated deep penetrating sealer that prevents moisture from entering the stone from below after it has been laid. It may be used for interior or exterior application.



### Areas of Application:

It can be used on the bottom surface of all natural and composite stones such as marble, granite, limestone, sandstone, terrazzo, concrete etc.



### Technical Data

Coverage: 1-15m<sup>2</sup>/Ltr depending upon the absorption coefficient of the stone.  
Shelf Life: 2 years



### Color

Colorless.



### Instruction for Use

1. Clean the surface with SURIE POLEX Floor Cleaner-Neutral. The surface must be absolutely clean and dry before application.
2. Prepare a small test patch to check coverage.
3. Shake the container before using. Do not dilute or mix with other products.
4. Apply evenly and fully with a brush, roller, sponge, spraying device or fluff free cloth. Remove surplus material with suitable cloth or fabric.
5. To ensure deep penetration apply 2 to 3 coats.
6. Repellency begins after a few minutes but the product is fully cured after 24 hours.
7. After the cure period the stone can be laid on the floor.



### Packaging

Available in 1 Ltr cans.



### Disclaimer

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check. Surie Poxlex accepts no liability for improper use of its products.