

## MADE IN INDIA

### Technical Data Sheet

# DENSI-HARD<sup>®</sup> MARBLE

## PREMIUM MARBLE DENSIFIER



### Description:

Surie Porex Densi-Hard Marble it is a premium marble densifier. It is a specially formulated water-based liquid that penetrates into the marble and solidifies to make the marble hard and dense. The process of densification makes the marble more durable and abrasion resistant of all type marble surfaces.



### Coverage

The coverage is determined by the porosity of the floor. It may be anywhere between 20-60 sqft per liter. A floor that has been previously hardened will require less material than a fresh floor.



### Application surfaces

- Marble floors interior and exterior
- Hotels
- Warehouses
- Industries area
- Food storage areas
- Commercial and residential areas



### Instruction for Use

1. Clean the surface properly to check the condition of the floor.
2. Start grinding the concrete with 36 or 60 grit depending upon your floor and grind up to 200grit resin bond. Grinding flattens the surface and opens up the surface ensuring better penetration.
3. Shake well before applying. Do not dilute with water. Apply Densi-Hard Marble evenly at the rate of approximately 20-60 sqft per litre. Lightly broom out any puddles immediately after the material has been applied. Allow material to remain on the surface for 20-30 minutes. Don't let the material dry until you have applied the second coat.
4. Let the material cure for 24 hours for best results.
5. Then proceed with 400 grit, 800 grit and go up to 1500 grit as required.
6. Remove all polishing dust and debris using a scrubbing machine.
7. Burnish with a 3000 grit Diamond Dot Pad for high gloss as required.



### Features

- Densifies, dustproofs and seals
- Water-based, odourless
- Low VOC
- Increases abrasion resistance
- Reduces water penetration
- Eligible for LEED points



### Technical Data

**Coverage:** The coverage is determined by the porosity of the floor. It may be anywhere between 20-60 sqft per litre. A floor that has been previously hardened will require less material than a fresh floor.

**Shelf Life:** 1 year



### Packaging

Available in 1L, 5 L, 10L & 20L Jerry can and 209L Barrel



### Precautions:

Protect from freezing. Store in a cool and dry place. Cover adjoining metal, brick, wood, glass and painted surfaces before spraying.



### Warranty

Surie Porex Industries LLP solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Surie Porex Industries LLP no other representations or statements made by Surie Porex Industries LLP or its representatives, in writing or orally, shall alter this warranty. Surie Porex Industries LLP make no warranties, implied or otherwise, as to the merchantability or fitness for ordinary or particular purposes of its products and excludes the same. If any Surie Porex Industries LLP product fails to conform to this warranty, Surie Porex Industries LLP will replace the product at no cost to the Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any installation of Surie Porex Industries LLP products which fails to conform to such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Surie Porex Industries LLP's products for the Buyer's intended purposes.