

Technical Data Sheet

GROUT SEALER



Description

Grout Sealer is an entry-level alternative to impregnating/penetrating sealers. It resists water absorption that can lead to salt, ion intrusion and freeze/thaw damage. It also provides basic protection against stains while drying invisible.



Areas of Application

It is a premium, solvent-based, deep penetrating sealer that offers maximum protection against dirt, oil & water based stains on cement joints for ceramic tiles, vitrified tiles and natural stone. It allows moisture vapor transmission and is UV resistant. It may be used for interior and exterior applications.



Features

- Easy-to-use
- Low cost
- Protects against dirt, weather, stain. water, and oil
- Slip resistant
- Freeze/thaw resistant
- Interior & exterior applications
- UV resistant
- Solvent-based & deep penetration



Instruction for Use

1. Surface must be dry and free of contaminants, including previously applied sealers, dirt, lime & hard water deposits, efflorescence, rust and grime.
2. Shake the container before using. Do not dilute or mix with other products.
3. Do not apply in direct sunlight. For exterior applications, do not apply if rain is expected within 24 hours. Use in a well ventilated area.
4. Apply Grout Sealer to the surface only of your substrate prior to grouting. This step will allow quick and easy cleanup after grouting.
5. To apply the Grout Sealer using a small size paint brush or a lint free cotton cloth.
6. Apply enough to wet the surface. Be careful not to saturate the open grout joints.
7. Grout Sealer to stand for approximately 3-5 minutes for maximum penetration.
8. Apply another application after the previous application has dried 2-3 hours.
9. Once the grout has completely cured, proceed with the sealing of the grout for water and stain .



Suitable Surface

- Ceramic Tile
- Porcelain Tile
- Granite
- Marble
- Stone

MADE IN INDIA

Technical Data Sheet



Technical Data

Coverage: 200 – 1,500 1/Ltr depending upon the absorption coefficient of the grout.
Shelf Life: 2 years



Color

Color - Transparent



Packaging

Available in 1 Ltr & 5 Ltr



Maintenance

After the sealing of treated surface / grout use Surie Porex floor cleaner neutral to cleaned of the stubborn dirt and it can be used daily maintenance.



Disclaimer

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check. Surie Porex accepts no liability for improper use of its products.