

## Technical Data Sheet

# SP-1 LIQUID CRYSTALLIZER



### Description

Use for maintenance of marble & limestone floors. Used a steel wool pad and a single disc machine the product provides a high gloss on marble and other calcareous stones. By crystallizing marble floors they get more wear resistant and the acid sensitivity is reduced. Can also be used to re-crystallize traffic areas of previously treated floors.



### Areas of Application

SP-1 is applied with a single disc machine and steelwool/white pads. Sparingly (max. 2-3 triggers of the spray device/m<sup>2</sup>) apply the product with a spray device or a hand sprayer and distribute with a single disc machine (150-200 rpm) by moving in circular motions until thoroughly absorbed and dry. A slight shine will be achieved. If a shinier surface is preferred, recrystallize the area once more with 3 triggers/m<sup>2</sup> and distribute with a single disc machine until thoroughly absorbed, dry and shiny. All abrasives and pad residue must be removed after crystallization by careful damp mopping or wet cleaning with Surie Porex Floor Cleaner Neutral. If a deeper shine is desired, the floor can then be buffed with a white pad and a high speed Burnisher.



### Instruction for Use

**Diluted:** The product is ready to use and should not be diluted.

**Preparation:** Remove all oil, wax, grease residue with Surie Porex Floor Cleaner Neutral. Completely remove any old wax and polish build-up with a stripper, thoroughly rinse the floor with water and allow to dry completely.



### Maintenance

**Maintenance:** Damp mopping: Clean heavily soiled floor with Surie Porex Floor Cleaner Heavy Duty. Do not use any products containing wax, soap or acrylates.